

# WatchGuard® XTM 5 Series

WITH A NEXT-GENERATION WATCHGUARD XTM 5 SERIES SOLUTION, YOUR NETWORK IS:

## RECOMMENDED FOR SMALL TO MIDSIZED BUSINESSES

WatchGuard XTM 5 Series appliances deliver a new class of performance-driven security for growing businesses. The 5 Series offers up to 2.6 Gbps firewall throughput and security features including full HTTPS inspection, VoIP support, and optional application control. Organizations that want room to easily scale their network security can move up to greater performance, more users, and additional security and networking features to meet escalating demands, without costly hardware replacements.

## WHY BUY AN ALL-IN-ONE SOLUTION?

An all-in-one XTM network security solution integrates complete protection while slashing the time and cost associated with managing multiple single-point security products. All security capabilities work together for a holistic, comprehensive approach to network protection. Your IT staff has more time to focus on other areas of network administration, and your business saves money on support and hardware costs.

This WatchGuard security appliance  
"can handle the growth.  
It's an excellent piece  
of hardware."

*Frank Curello  
Chief Executive Officer  
GameWear*



## SECURE

- Application-layer content inspection recognizes & blocks threats that stateful packet firewalls cannot detect.
- Wide-ranging proxy protection provides robust security on HTTP, HTTPS, FTP, SMTP, POP3, DNS, TCP/UDP.
- A suite of security subscriptions boosts protection in critical attack areas for complete threat management.
- Optional Application Control keeps unproductive, inappropriate, and dangerous applications off-limits.

## FAST and EFFICIENT

- Up to 2.6 Gbps firewall throughput and up to 750 Mbps VPN throughput keep data moving.
- Best UTM throughput in its class, even with strong security enabled.
- Gigabit Ethernet ports support high-speed LAN backbone infrastructures & gigabit WAN connections.
- Active/active high availability with load balancing ensures maximum network uptime.
- Interactive, real-time monitoring and reporting – at no additional charge – give an unprecedented view into network security activity so you can take immediate preventive or corrective actions.
- Intuitive management console centrally manages all security functions.
- Drag-and-drop Branch Office VPN setup – three clicks and your remote office is connected.

## FLEXIBLE

- WAN and VPN failover provide redundancy for increased reliability.
- Multiple VPN choices deliver flexibility in remote access. Includes IPSec, SSL, and support for iOS devices such as iPhone, iPad, and iPod touch.
- To maximize port utilization, any of the seven ports can be configured as Trusted, External, or DMZ.
- Networking features, such as transparent bridge mode and multicast over VPN, allow you to add security without needing to change existing network infrastructure.

## SCALABLE

- Add powerful security subscriptions to block spam, control dangerous and inappropriate application usage and web surfing, prevent network intrusions, and stop viruses, spyware, and other malware at the gateway.
- Move up to the "Pro" version of the Fireware® XTM operating system for advanced networking features, including active/active high availability, VLAN support, multi-WAN and server load balancing, dynamic routing, and QoS.
- Upgrade to a higher model within the line for more performance and capacity with a simple license key.

## PREPARED FOR TOMORROW'S CHALLENGES

- No need to compromise protection for strong performance or vice versa. Multi-layered, interlocking security protects the network while throughput remains high.
- Advanced networking features ensure reliability and the flexibility to meet changing business requirements.
- Secure remote connectivity keeps the mobile workforce online and productive.
- Monitoring and reporting tools, included at no extra cost, support industry and regulatory compliance, with drill-down functions that make it easy to pinpoint specific activities.

XTM 5 Series	XTM 505	XTM 510	XTM 520	XTM 530
<b>THROUGHPUT &amp; CONNECTIONS</b>				
Firewall throughput*	1.5 Gbps	1.8 Gbps	2.2 Gbps	2.6 Gbps
VPN throughput*	210 Mbps	350 Mbps	550 Mbps	750 Mbps
AV throughput*	520 Mbps	625 Mbps	760 Mbps	900 Mbps
IPS throughput*	500 Mbps	600 Mbps	735 Mbps	870 Mbps
Aggregate XTM throughput*	330 Mbps	395 Mbps	480 Mbps	570 Mbps
Interfaces 10/100	1 copper	1 copper	1 copper	1 copper
Interfaces 10/100/1000	6 copper	6 copper	6 copper	6 copper
I/O interfaces	1 Serial/2 USB	1 Serial/2 USB	1 Serial/2 USB	1 Serial/2 USB
Nodes supported (LAN IPs)	Unrestricted	Unrestricted	Unrestricted	Unrestricted
Concurrent connections (bi-directional)	40,000	50,000	100,000	350,000
New connections per second	12,000	12,000	12,000	12,000
VLANs bridging, tagging, routed mode	75	75	75	75
WSM licenses (incl)	4	4	4	4
Local user database	500	500	1,000	2,500
<b>VPN TUNNELS</b>				
Branch Office VPN	65	75	200	600
Mobile VPN IPsec (incl/max)	5/75	25/100	50/300	400/1,000
Mobile VPN SSL	1/65	1/75	1/300	1/600

<b>SECURITY FEATURES</b>	
Firewall	Stateful packet inspection, deep packet inspection, proxy firewall
Application proxies	HTTP, HTTPS, SMTP, FTP, DNS, TCP, POP3
Threat protection	Blocks spyware, DoS attacks, fragmented packets, malformed packets, blended threats, and more
VoIP	H.323, SIP, call setup and session security
Security subscriptions	Application Control, Gateway AntiVirus, Reputation Enabled Defense, WebBlocker, spamBlocker, Intrusion Prevention Service

<b>VPN &amp; AUTHENTICATION</b>	
Encryption	DES, 3DES, AES 128-, 192-, 256-bit
IPSec	SHA-1, MD5, IKE pre-shared key, 3rd party cert
VPN failover	Yes
SSL	Thin client, Web exchange
PPTP	Server and Passthrough
Single sign-on	Transparent Active Directory Authentication
XAUTH	RADIUS, LDAP, Windows Active Directory
Other user authentication	VASCO, RSA SecurID, web-based, local

<b>MANAGEMENT</b>	
Management platform	WatchGuard System Manager (WSM)
Alarms and notifications	SNMP v2/v3, Email, Management System Alert
Server support	Logging and Reporting with Server Health status, Quarantine, WebBlocker, Management
Web UI	Supports Windows, Mac, Linux OS
Command line interface	Includes direct connect and scripting

<b>STANDARD NETWORKING</b>	
QoS	8 priority queues, DiffServ, modified strict queuing
IP address assignment	Static, DHCP (server, client, relay), PPPoE, DynDNS

<b>CERTIFICATIONS</b>	
Security	ICSA Firewall, ICSA IPsec VPN, CC EAL4+ Review Pending: FIPS 140-2
Safety	NRTL/C, CB
Network	IPv6 Ready Gold (routing)
Control of hazardous substances	WEEE, RoHS, REACH

\*Throughput rates will vary based on environment/configuration. Contact your WatchGuard reseller or call WatchGuard directly (1.800.734.9905) for help determining the right model for your network.

**U.S. SALES** 1.800.734.9905 **INTERNATIONAL SALES** +1.206.613.0895

[www.watchguard.com](http://www.watchguard.com)

No express or implied warranties are provided for herein. All specifications are subject to change and expected future products, features or functionality will be provided on an if and when available basis. © 2012 WatchGuard Technologies, Inc. All rights reserved. WatchGuard, the WatchGuard logo, Fireware, and LiveSecurity are either trademarks or registered trademarks of WatchGuard Technologies, Inc. in the United States and/or other countries. All other tradenames are the property of their respective owners. Part No. WGC66650\_051812

## POWERED BY FIREWARE XTM

Every XTM 5 Series appliance ships with the Fireware XTM operating system. As network requirements become more complex, it's easy to upgrade to the Pro version of the OS with a simple software license key.

NETWORKING FEATURES	FIREWARE XTM	FIREWARE XTM PRO
Routing	Static, dynamic routing (RIP)	Dynamic (BGP4, OSPF, RIP v1/2), Policy-based
High Availability	-	Active/passive, active/active with load balancing
NAT	Static, dynamic, 1:1, IPsec traversal, policy-based	Virtual IP for server load balancing
SSL	1 SSL tunnel available	Maximum number of SSL tunnels available
Other Features	Port Independence, transparent/drop-in mode, multi-WAN failover	Server load balancing, multi-WAN load balancing

## DIMENSIONS AND POWER

Product Dimensions	11.25" x 17" x 1.75" (28.6 x 43.2 x 4.5 cm)
Shipping Dimensions	18" x 21" x 5.25" (45.7 x 53.3 x 13.3 cm)
Shipping Weight	16.1 lbs (7.3 Kg)
AC Power	100-240 VAC Autosensing
Power Consumption	U.S. 50 Watts (max), 171 BTU/hr (max)
Rack Mountable	1U rack mount kit included

ENVIRONMENT	OPERATING	STORAGE
Temperature	32° F to 104° F 0° C to 40° C	-40° F to 158° F -40° C to 70° C
Relative Humidity	10% to 85% non-condensing	10% to 95% non-condensing
Altitude	0 to 9,843 ft at 95° F (3,000 m at 35° C)	0 to 15,000 ft at 95° F (4,570 m at 35° C)
MTBF	51,644 hours @ 77° F (25° C)	



## EXPERT GUIDANCE AND SUPPORT

An initial subscription to LiveSecurity® Service is included with every XTM 5 Series appliance. LiveSecurity provides hardware warranty with advance hardware replacement, 12/5 or 24/7 technical support, software updates, and concise threat alerts.

## BUY THE BUNDLE AND GET THE WORKS!

Get everything you need for complete threat management at a great price with the Security Bundle. Includes choice of 5 Series appliance, plus Application Control, Intrusion Prevention Service, Reputation Enabled Defense, Gateway AntiVirus, WebBlocker, spamBlocker, and LiveSecurity Service with 24/7 tech support.

